LIFETIME

DURABILITY OF ROPES

The durability of a rope depends above all on the way it is used, but also on numerous technical factors: The quality of yarn used ; the compactness of the rope ; its suppleness ; the braiding of the filaments of the sheath ; their twist ; their number ; the number of braids...



the number of braids... One other factor plays a particularly important role: the thickness of the sheath. You can check the quantity of sheath in BEAL ropes thanks to the percentage shown at the side of this pictogram.

I LIFETIME OF BEAL METALLIC PPE

The lifetime of metal PPE is not limited.

ATTENTION :



This is the potential lifetime in use. A metal item of PPE may be destroyed during its very first use. It's inspection and control which determine if the product must be scrapped earlier. Between uses, appropriate storage is essential.

LIFETIME OF BEAL PLASTIC AND TEXTILE PPE



5 YEARS STORAGE TIME

In good storage conditions plastic and textile BEAL PPE may be stored for up to **5 years** before first use, without affecting their future lifetime in use.

10 YEARS LIFETIME IN USE



The potential lifetime of plastic and textile BEAL PPE in use is up to a maximum of **10 years**.

ATTENTION :

This is the potential lifetime in use. An item of PPE may be destroyed during its very first use. It's inspection and control which determine if the product must be scrapped earlier. Between uses, appropriate storage is essential.

15 YEARS LIFETIME



The maximum lifetime of plastic and textile BEAL PPE is up to **15 years**. Lifetime = Time in storage + time in use.

SUMMARY

SERVICES												p. 2	
ROPES													

ROPES FOR DIFFICULT AREA ACCESS	à6
UNIVERSAL ROPE TO BOTH STANDARDS	p. 7
FLOATING ROPE	р. 7
DYNAMIC ROPES	p. 7
RESCUE ROPES	p. 8
ROPES RESISTANT TO HIGH TEMPERATURES	p. 9
ROPES RESISTANT TO CHEMICAL PRODUCTSp	. 10
LIGHTWEIGHT ROPES	. 11
SPECIAL ROPESp	. 11
ROPES FOR TREE WORK p. 12	-13

SLINGS / ANCHORS

SLINGS	 	 	 		 	p	. 15
ACCESSORY CORDS AND WEBBING		 	 		 	p	. 15
ANCHORS	 	 	 		 	p	. 16

LANYARDS

FALL ARREST LANYARDS											Э.	17
DYNAMIC LANYARDS	 				 						Э.	18
LANYARDS					 						э.	19

HARNESS

 FALL ARREST, ROPE ACCESS AND WORK POSITIONING
 ...
 p. 20-21

 WORK POSITIONING AND ROPE ACCESS
 ...
 p. 22-23

 FALL ARREST AND WORK POSITIONING
 ...
 p. 24-25

HELMET

WORK AT HEIGHT, RESCUE AND FOR INDUSTRY p. 26-27

METAL

p. 28-29 p. 30 p. 31-32 p. 32 p. 33 p.34-35 p. 36-37
p. 38-40
p. 41
p. 42-45
р. 46-47
p. 48





IDENTIFICATION

IDN UNIQUE NUMBER



All BEAL PPE is marked with a unique number which, in addition to providing the year of manufacture, ensures traceability of the product.

BCC BEAL COLOR CODE



BEAL slings, pre-cut ropes and lanyards are either embroidered or have a line of stitching which -dependant on the colour useddepicts the year of manufacture of the product.

TRACEABILITY, IDENTIFICATION, TIP PERSONALISATION

Harnesses, lanyards, energy absorbers, ropes with sewn terminations are supplied with a TIP label (traceability, identification and personalisation). TIP allows you to identify an item by writing your name and personalising the unique number of your PPE. The TIP also has a QR code and web link to instantly access the item's logbook online, promoting its management. It equally allows for a new generation RFID chip, called NFC, to be stuck to the label as an add-on.



D 0 1 B 0 0 F 0 1 0 5 1 4



The colour of the internal thread identifies the year of manufacture.

BEAL INSPECT PPE MANAGEMENT

www.beal-inspect.com is a PPE management website. By using responsive technology from whichever phone, tablet or computer (connected to the internet) it is able to store logbooks, your documents as well as user instructions in the 'cloud' and to share these between terminals.

Regardless of the make of your PPE, you can log all inspections, become notified of their forthcoming inspections and share information between terminals (smartphone, tablet, PC and Mac) as well as other people who have been given authorisation.





HARNES

A



≤ß

SERVICES

CUSTOMIZATION

INFC NEAR FIELD CONNECTION

NFC is a new standard in RFID chips, ultra compact and flat, compatible with most new generation Smartphones. By bringing your phone close to the NFC chip, information relating to the item of PPE can be accessed directly and wirelessly without the need for specific software, similar to wireless payments which are already becoming commonplace. All PPE equipped with a TIP label can accommodate a NFC chip to allow kit management via smartphone.

The rear of the waist belt contains an area to allow personal marking such as your company's name, as well as a QR code which allows a personal identifier to be generated (your name and unique ID).



C Brace NFC





ROPES FOR DIFFICULT AREA ACCESS



Thanks to the UNICORE Process, Access ropes reach a new level in security. – In effect, the UNICORE Process integral to this 10.5 mm rope will secure most delicate operations, – whilst retaining lightness and flexibility.











Ref. blue: BCSA105.100.B (100m) / BCSA105.200.B (200m) / BCSA.105.500.B (500m) orange: BCSA105.100.0 (100m) / BCSA105.200.0 (200m) / BCSA.105.500.0 (500m)





UNICORE as standard, bonding core and for maximum security in all situations. ——











Ref. red: BCSA11.100.R (100m) / BCSA11.200.R (200m) / BCSA11.500.R (500m) yellow: BCSA11.100.Y (100m) / BCSA11.200.Y (200m) / BCSA11.500.Y (500m)

ANTIPODES 10,5 mm

Very tough, this is the established standard rope for work at height. Same construction as the INDUSTRIE 10.5 mm.







Ref. white: BCS105.50 (50m) / BCS105.100 (100m) / BCS105.200 (200m) / BCS105.500 (500m)

ANTIPODES 11,5 mm

Great abrasion resistance for the most demanding applications.











Ref. white: BCS115.100 (100m) / BCS115.200 (200m) red: BCS115.200.R (200m)

ROPES FOR DIFFICULT AREA ACCESS

IdN

j.

10

CE

IdN

j1 Туре

10

CE

А t

74 g

36 %

3400 daN (kg)

2400 daN (kg)

EN 1891

А Ŧ

65 g

38 %

3000 daN (kg)

2400 daN (kg)

EN 1891

Туре

Weight per metre

Breaking load

% of the sheath

Strength with

sewn terminations

Weight per metre

Breaking load

% of the sheath

Strength with sewn terminations

I INDUSTRIE 10,5 mm

This rope is specially adapted to the requirements of work at height companies.



Ref. white with sewn termination: BCSI105.10TERM (10m) / BCSI105.20TERM (20m) /BCSI105.30TERM (30m) / BCSI105.40TERM (40m) / BCSI105.50TERM (50m) / BCSI105.60TERM (60m)

I INDUSTRIE 11 mm

An ideal rope with no diameter restrictions for security in work at height.

C€ EN 1891 - **idN** voitto Ref Ref. Sewn termination: Sewn terminations white with sewn termination: BCS111.10TERM (10m) / BCS111.20TERM (20m) / BCS111.30TERM (30m) / BCS111.40TERM (40m) / BCS111.50TERM (50m) / BCS111.60TERM (60m) red with sewn termination: BCS111.10TERM.R (10m) / BCS111.20TERM.R (20m) / BCS111.30TERM.R (30m) / BCS111.40TERM.R (40m) / BCS111.50TERM.R (50m) / BCS111. 60TERM.R (60m) Sewn terminations

INDUSTRIE 12 mm

An ideal work at height rope when a large rope diameter is required for greater security.

CE EN 1891 - İdn







Ref. white: BCSI12.200 (200m) / red: BCSI12.200.R (200m)

CONTRACT 10,5 mm

Type A rope with the optimum balance quality/ price.



IdN ***** Туре А 66 g Weight per metre 1 2700 daN (kg) Breaking load J W % of the sheath 0 39 % CE EN 1891



Ref. white: BCS105C.20 (20m) / BCS105C.30 (30m) / BCS105C.40 (40m) / BCS105C.50 (50m) / BCS105C.60 (60m) / BCS105C.800 (80m) / BCS105C.100 (100m) / BCS105C.200 (200m) / BCS105C.500 (500m)

ROPES



≤ß> 5



<BEAL

C 101

SBEALS

Ref white: BCS111.50 (50m) / BCS111.100 (100m) / BCS111.200 (200m) / BCS111.500 (500m) red: BCS111.50.R (50m) / BCS111.100.R (100m) / BCS111.200.R (200m) / BCS111.500.R (500m) blue: BCS111.50.8 (50m) / BCS111.100.8 (100m) / BCS111.200.B (200m) / BCS111.500.8 (500m)

SACALS











Ref. white: BCSPW11.200 (200m)





Security rope which conforms to 2 standards, both the semi-static and the dynamic rope standards.



CAREFUL : a slippage between core/sheath can happened when it is used with a descender

UNICORF





Ref. black & yellow: BCDS105.50 (50m) / BCDS105.60 (60m)



UNICORE Dynamic ropes cushion impacts and must be used

-**CE** EN 1891 - **İdn**

during certain procedures to absorb the energy of possible falls.









ROPES

Ref. green: BC105T50.G (50m) / BC105T.60.G (60m) / BC105T.70.G (70m) / BC105T.200.G (200m) blue: BC105T50.B (50m) / BC105T.60.B (60m) / BC105T.70.B (70m) / BC105T.200.B (200m)

APOLLO II 11 mm

Dynamic ropes cushion impacts and must be used during certain procedures to absorb the energy of possible falls.

- CE EN 892 - İdn





Ref. red: BC11A.50.R (50m) / BC11A.60.R (60m) / BC11A.200.R (200m) anise: BC11A.50.A (50m) / BC11A.60.A (60m) / BC11A.200.A (200m)





RESCUE ROPES



Semi-static type A rope with a polyester sheath. Its fluorescent orange colour make it particularly suited for use in rescues.







Ref. orange: BCSR105.200 (200m)

I RESCUE VLS 11,3 mm

The Rescue VLS is a very low stretch rope designed for technical rope rescue. VLS for Very Low Stretch.

Elongation 50-150kg : 0,8%











Ref. yellow Fluorescent: BCSR113.200.Y (200m) black: BCSR113.200.BK (200m)

REACTIVE 10,5 mm

A specialist rope for rescues in low light conditions. Highly visible as soon as a light source is pointed towards it thanks to a reflective yarn that is woven through the sheath.

[▲] Warning

The reflective yarn is very fragile and wears rapidly when subjected to abrasion, although it maintains its reflective properties. Its wear does not affect the rope's strength



di di di







RESCUE HALF INCH IdN 13 mm Туре А 5 Rope for rescue teams using American methods. Weight per metre 65 g Breaking load 4400 daN (kg)





Ref. White, orange: BCSR13.300 / BCSR13.50

- CE EN 1891 - **idn**

-

ROPES RESISTANT TO HIGH TEMPERATURES



EFFECT OF HIGH TEMPERATURES ON ARAMID

The resistance of Aramid to high temperatures is best illustrated by the graph illustrating the residual strength after exposure to raised temperatures. Thus we may for example see that after 10 hours of exposure at 200° C it retains 100 % of its strength, or that after 1 hour at 350° C it retains 90 % of its strength.

TEST WITH BLOWTORCH

Semi-static rope holding a mass of 100 kg exposed to a temperature of 400° C (+ or- 50° C) for 15 minutes.

Results:

- Classic 11 mm rope: Break after around 40 seconds. • RAIDER 11 mm rope: Residual strength around
- 1500 daN after 15 minutes.
- RAIDER TACTIC 11 mm rope: residual strength around 1000 daN after 15 minutes.

TEST AGAINST A RED HOT BAR

The rope supports a 100 kg mass.

It is held clear of a 25 mm bar heated red-hot. It is released against the bar and the time to rupture measured.

- **Results:**
- Classic 11 mm rope: 3 seconds
- HOTLINE 11 mm: 5 seconds
- RAIDER TACTIC 11 mm: 8 seconds
- RAIDER 11 mm: 18 seconds



ROPES

Relationship between time of exposure at high temperature and residual strength of Aramid.



RAIDER 10,5 mm

Sheath Aramic

Aramid

S. ...

Semi-static Type B rope with an Aramid sheath capable of withstanding a long period close to a major source of heat.

CE EN 1891 - İdn

Core







Ref. black: BCSK105R.200 (200m)





Sheath Aramid Core CE EN 1891 - İdn Aramid





Ref black: BCSK11RT200 (200m)



p1-19 RopesLanvards 2018.indd 9





CHEMICAL RESISTANCE OF **ARAMID YARN**

(exposure for 100 hours)

ACIDS	Residual Tenacity in %age
Hydrochloric 20 % at 20° C	98 %
Nitric 10 % at 20° C	99 %
Sulphuric 20 % at 95° C	93 %
Sulphuric 40 % at 95° C	89 %
Acetic 40 $\%$ at 95° C	97 %
Formic 90 % at 95° C	82 %

Residual lenacity in %age
75 %
93 %
100 %

Other Chemical Products	Residual Tenacity in %age
Petrol / Gas	98 %
Benzene	98 %
Methyl Ethyl Cetone	97 %
Ethylene Glycol	94 %
Phenol	95 %
Sea water	100 %



HOTLINE 11 mm

Semi-static rope with an interior sheath in Aramid, covered by a classic sheath. HOTLINE rope allows access in the presence of certain dangerous chemicals.

- CE EN 1891 - İdn







RESISTANT

RAIDER 11 mm

Sheath Aramid

Aramid

S: .

Aramid

Semi-static Type B rope with an Aramid sheath capable of withstanding a long period close to a major source of heat.

C€ EN 1891 - idN

Core







Ref. white: BCSK11.200 (200m)



white: BCS09.100 (100m) / BCS09.200 (200m) red: BCS09.100.R (100m) / BCS09.200.R (200m)

Ref.

Ref.



Semi-Static type B rope, ultra light, but necessitating great care during use.







The lightest of the type A ropes with a margin of security sufficient for some industrial uses.

▲___C€ EN 1891 - İdN





ROPES







SPECIAL ROPES

white: BCS10.100 (100m) / BCS10.200 (200m) red: BCS10.100.R (100m) / BCS10.200.R (200m)

AUSTRALIS 11,5 mm

Specially developed to meet the requirements of Australian standard AS4143.3, this very low stretch rope has a sheath in polyester and is constructed like the American ropes.

Reduction in shrinkage (polyester).
 Better heat resistance (Melting point of

Better abrasion resistance due to a thick







Ref. BCSA115.200

| **ERGO** 12,5 mm

STRONG POINTS

sheath.

polyester 260° C).

Designed to meet the needs of firefighters in their different tasks, conforming to civil security code NIT no. 129-83-92 and to the Standard EN 1891.







Ref. white: BCS125.30 (30m) / BCS125.60 (60m) / BCS125.100 (100m) / BCS125.200 (200m)



/////

<<mark>₿</mark>> 11

BILOBA 11,5 mm

A lightweight arborist rope specially designed for use with mechanical Prusiks. Its double braided construction makes the rope particularly supple. Fluorescent colours ensure the rope is highly visible.











Ref. orange & vellow: BCSE115.200 (200m)

Ker orange & yellow: BCSE 15.200 (200m) orange & yellow with seven termination: BCSE115.20TERM (20m) / BCSE115.30TERM (30m) / BCSE115.35TERM (35m) / BCSE115.40TERM (40m) / BCSE115. SOTERM (50m) / BCSE115.15.60TERM (60m) orange & yellow with two ending: BCSE115.20TERM (20m) / BCSE115.30TERM (30m) / BCSE115.35TERM (35m) / BCSE115.40TERM (40m) / BCSE115.50TERM (50m) / BCSE115.60TERM (60m)

GINKGO 12 mm

Made along the same lines as the BAOBAB, its thinner diameter makes a lighter rope, more supple and easier to handle than BAOBAB. It benefits from a new, glueless procedure for bonding the sheath onto the core, preventing all slippage, but still allowing splices to be made.

CE EN 1891 - idn







Ref. black & yellow: BCSE12.200 (200m) Ket. Diack & yellow: BCSE12.200 (200m)
black & yellow with sewn termination: BCSE12.20TERM (20m) / BCSE12.30TERM (30m) / BCSE12.35TERM (35m) / BCSE12.40TERM (40m) / BCSE12.50TERM (50m) / BCSE12.60TERM (60m)
black & yellow with two ending: BCSE12.20TERM2 (20m) / BCSE12.30TERM2 (30m) / BCSE12.35TERM2 (35m) / BCSE12.40TERM2 (40m) / BCSE12.50TERM2 (30m) / BCSE12.60TERM2 (35m) / BCSE12.40TERM2 (40m) /



BAOBAB 13,5 mm UNICORE

Its braiding results from the technology of American tree workers, giving it great qualities of strength, pliability and easy handling.

The UNICORE process which bonds the core and sheath prevents sheath slippage during use with self-loacking loops.



IdN j1 А Туре . Weight per metre 119 g Breaking load 3000 daN (kg) % of the sheath 10 82 % Strength with sewn terminations 2300 daN (kg) CE EN 1891



Ref. red & white: BCSE135.200 (200m) red & white with sewn termination: BCSE135.20TERM2 (20m) / BCSE135.30TERM2 (30m)

BONSAÏ 13 mm

This multi-use rope, with an excellent handling/ solidity balance, allows you to undertake all types of tree work in full security.









Ref. blue & white: BCSE13 200 (200m) Blue & white with sewn termination: BCSE13.20TERM (20m) / BCSE13.30TERM (30m) / BCSE13.40TERM (40m) / BCSE13.50TERM (50m)

BCSE13.30TERM (3011) Blue & white with two sewn terminations: BCSE13.20TERM2 (20m) / BCSE13.30TERM2 (30m) / BCSE13.40TERM2 (40m) / BCSE13.50TERM2 (50m)

≤ß≥ 12



Short lengths of rope with sewn terminations for constructing self-locking (prusik) loops. These ropes have a 50 % aramid construction intermixed with polyester filaments. Prusiks made from classic ropes have a very short life, because they glaze in use due to the effect of friction. The presence of 50 % of highly thermally resistant aramid fibres in VOLCANO protect it against melting and thus greatly increases its lifetime. Available in 10 and 12 mm, and 70 and 90 cm lengths, to suit different types

of knots.



RETENTION ROPES

Weight per metre

Ref. Red : BCSV08

ROPES FOR PRUSIKS

REGATE 10 mm

resistance, runs perfectly.

Weight per metr

Ref. yellow : BREG10.100 (100m)

Its double braid polyester serves to make prusik loops. This 10 mm diameter rope, with high abrasion

IdN

CE

| VOLCANO 8 mm

75 g

48 g

CE EN 564

The regulations require the application of a coefficient of 7 to all lifting ropes. Breaking load divided by 7 = WLL (Working Load Limit). The weight of the branches must not exceed the Working Load Limit for dismantling in total security. BEAL retention ropes are colour coded by diameter and thus by strength in order to avoid errors.







ROPES

Model	Standard	Certification	Type	Breaking load	Strength with Figure-of-8 knot	Strength with sewn terminations	Number of fall factor 1	Impact force factor 0.3	Extension 50/150 kg	Sheath slippage	Weight per metre	% of the sheath	Mass of the core	Shrinkage in water	Material
ROPES FOR DIFFICUL	T AREA A	CCES	SS												
ACCESS 10,5 mm UNICORE	EN 1891	CE	A	3000 daN(kg)	1800 daN(kg)	2400 daN(kg)	12	5,3 kN	3 %	0 %	65 g	38 %	62 %	2,5 %	Polyamide
ACCESS 11 mm UNICORE	EN 1891	CE	A	3400 daN(kg)	1950 daN(kg)	2400 daN(kg)	20	5,6 kN	2,1%	0%	74 g	36 %	64%	1,1%	Polyamide
ANTIPODES 10,5 mm	EN 1891	CE	A	3000 daN(kg)	1800 daN(kg)	2400 daN(kg)	12	5,3 kN	3 %	0,8%	65 g	38%	62 %	5%	Polyamide
ANTIPODES 11,5 mm	EN 1891	CE	A	3500 daN(kg)	2200 daN(kg)	2600 daN(kg)	>20	5,6 kN	2,6 %	0,5 %	78g	38%	62 %	5%	Polyamide
INDUSTRIE 10,5mm	EN 1891	CE	A	3000 daN(kg)	1800 daN(kg)	2400 daN(kg)	12	5,3 kN	3%	0,8%	65 g	38%	62%	5%	Polyamide
INDUSTRIE 11 mm	EN 1891	(E	A	3400 daN(kg)	1950 daN(kg)	2400 daN(kg)	16	5,6 KN	2,1%	0,8%	/4g	36%	64%	1,1%	Polyamide
INDUSTRIE 12mm	EN 1891	CE	A	4200 daN(kg)	2200 daN(kg)	3000 daiN(kg)	>20	5,6 KN	2,5%	0,3 %	94 g	34 %	66%	2,4%	Polyamide
CONTRACT 10,5mm	EN 1891	CE	A	2700 daN(kg)	1000 daN(kg)	- 2400 daNi/ka)	>5	5,5 KIN	2,9%	0%	00 g	39%	61%	3,3%	Bolyamida
TOR WORK 10 Emm	EN 1091	CE	A	3200 uaiv(kg)	1700 daN(kg)	2400 uaiv(kg)	10		4,2	0.20/	/ Iy	JJ70	0070 EC 0/	4 % 2 E 0/	Folyallilue
NORTH SEA 11 mm	EN 1891	CE	Δ	2000 daN(kg)	1800 daN(kg)	2200 daN(kg)	16	5.6kN	4,0 %	0,5 %	75a	44 /0	56%	3,5%	
DYNAMIC ROPES	ENTIO		7.	5000 dari(itg)	1000 dart(kg)	2200 dul1((kg)	10	5,0 111	170	0,5 /0	, sg	1170	50 /0	5 /0	
TOP GUN II 10,5 mm UNICORE	EN 892	CE	1	2100 daN(kg)	-	1700 daN(kg)	Factor 2	-	-	-	68 g	40%	60%	-	Polyamide
APOLLO II 11 mm	EN 892	CE	1)	2300 daN(kg)	-	-	Factor 2	-	-	-	75a	35%	65%	-	Polyamide
UNIVERSAL ROPE TO	BOTH ST	ANDA	RDS				16			1	. 5				,
DYNASTAT 10,5mm	EN 892 EN 1891	CE	A ①	2500 daN(kg)	1600 daN(kg)	1900 daN(kg)	24 Factor 2 10	4,3 kN	2 %	0,8%	75 g	44%	56%	0%	Sheath: Polyamide Core: Polyamide/ Vectran
FLOATING ROPE	EN 1001	CT.		2500 d- N/()	1000 d-N(lur)		F	E DIAL	2.6.0/	0.0/	00 -	22.0/	67.0/	0.0/	Deleveride (Newson
	EN 1891	CE	A	2500daN(kg)	1600 daN(kg)	-	5	5,3 KN	3,6%	0 %	80 g	33%	67%	0 %	Polyamide/ Neopren
RESCUE 10 5mm	ENI 1901	CE	Δ	2000 daN(ka)	1800 daN(ka)	2400 daN(ka)	12	5 2 k N	2.0/	0.8%	65 a	20.0/	62.0%	5.0/	Sheath: Polyester
	NEDA	CL CL			1000 uaii(kg)	2400 uaii(kg)	12	3,3 KN	5 /0	0,0 /0	0.59	10 /0	57.0/	5 /0	Core: Polyamide
RESCUE VLS 11,3 mm	NFPA	CE	A	3600 daiv(kg)	-	-	(2)	5 3 1 11	0,8 %		94 g	43 %	57%	4.000	Polyester
RESCUE REACTIVE 10,5 mm	EN 1891	CE	A	3000 daiN(kg)	1800 daiN(kg)	2400 dai\(kg)	12	5,3 KN	2,6%	0%	6/g	3/ %	63%	1,8%	Polyamide
RESCUE HALF INCH	EN 1891	CE	A	4400 daN(kg)	2400 daN(kg)	-	20	5,4 kN	2,9 %	0,2%	10/g	37%	63%	0,35%	Polyamide
PRO WATER 11mm UNICORE	EN 1891	(E MDE	A	2500 daN(kg)	1600 daN(kg)	-	5	5,3 KN	3,6 %	0 %	80 g	33%	67%	0 %	Polyamide/ Neopren
RUPES RESISTANT TU	ENI 1901		D	2200 doN(kg)	1800 daN(ka)	2200 daN(ka)	6	1.6KN	2 2 0/	0.%	60 a	22.0%	69.0%	0.5%	Sheath: Aramid
RAIDER 10,5 mm	EN 1001	CL	D	2500 dati(kg)	1000 d-N(kg)	2200 daN(kg)	0	4,0 KN	3,2 /0	0.0	039	JZ /0	50.0/	0,5 %	Core: Polyamide Sheath: Aramid
RAIDER 11 mm	EN 1891	CE	R	2600 dal\(kg)	1900 daiv(kg)	2200 daiN(kg)	8	4,7 KN	3,3%	0,6%	81g	41%	59%	0,5 %	Core: Polyamide Sheath: Aramid
RAIDER TACTIC 11 mm	EN 1891	CE	A	2400 daN(kg)	1800 daN(kg)	2200 daN(kg)	6	5,9 kN	3,2%	0 %	75 g	30 %	70%	0,5%	Core: Polyamide
KUPES RESISTANT TU	CHEIMIC		KUDU	2E00 doN(kg)	1000 doN(kg)	2200 daN(ka)	15	EGLN	2 1 0/	0.9/	70 a	12.0/	E O 0/	2.20/	Sheath: Polyamide
	EN 1891	CE	A		1900 dalv(kg)	2200 daiv(kg)	ci	3,0 KIN	3,1 %	0%	79g	42 %	50 %	3,3 %	Core: Polyamide/Aramid Sheath: Aramid
	EN 1891	CE	B	2600 dal\(kg)	1900 daiv(kg)	2200daN(kg)	8	4,7 KN	3,3 %	0,6 %	81g	41%	59%	0,5 %	Core: Polyamide
	ENI 1901	CE	D	2100 doN(kg)	1250 doN(kg)		0	4 kN	2.6%	0.2%	51 a	/12.0/	570/	1 0/-	Polyamido
	EN 1051	CL CL					-	5 0 1 11	5,0 %	0,5 %	51y	40 %	57.0	4 /0	r olyanide
	EN 1891	CE	A	2500 dalv(kg)	1600 daiN(kg)	-	5	5,3 KN	4,4 %	0 %	62 g	43 %	5/%	4 %	Polyamide
FRG0 12 5mm	ENI 1801	CE	Δ	3800 daN(ka)	2300 daN(ka)	2700 daN(ka)	> 20	5.6KN	2.0%	0%	101a	/13.0%	57%	3.7%	Polyamide
		CL	~		2300 uan(kg)	27000011(Kg)	20	3,0 KN	2,570	0 /0	02.7	43 //	50.00	5,7 /0	rolyanide
AUSTRALIS 11,5 mm	AS4143.3	-	-	3300 daiN(kg)	-	-	-	-	-	0 %	93,7 g	42%	58%	-	
BILOBA 11.5 mm	EN 1891	CF	Α	3000 daN(kg)	1800 daN(kg)	1800 daN(kg)	15	5 kN	3.8%	0%	89 a	44%	56%	2.8%	Sheath: Polyester
GINKGO 12mm	ENI 1901	CE		2700 daN(kg)	1600 daN(kg)	2200 daN(kg)	0	5.7 kN	1 0/-	0%	02 a	60%	21.0/	2,0 %	Core: Polyamide Sheath: Polyester
	LIN 1091		A	2700 udiv(kg)		ZZOU Udiv(Ky)	0	5,7 KN	4 /0	0 70	92 y	09 /0	51 /0	2,0 /0	Core: Polyamide Sheath: Polyester
BAOBAB 13,5mm UNICORE	EN 1891	CE	A	3000 daiN(kg)	1900 daiv(kg)	2300 daiN(kg)	20	5,1 KN	5%	0%	119g	82 %	18 %	2%	Core: Polyamide
BONSAI 13mm	EN 1891	CE	A	3400 daN(kg)	1800 daN(kg)	2500daN(kg)	20	5,3 KN	4,2%	0%	98g	61%	39%	4,5 %	Polyamide
INTERVENTION ROPES	-	CE	-	1700 uaiv(kg)	-	-	-	-	-	-	7 s y	-	-	-	Polyester
RAIDER 10,5 mm	EN 1891	CE	В	2300 daN(kg)	1800 daN(kg)	2200 daN(kg)	6	4,6 kN	3,2%	0%	69 g	32%	68%	0,5%	Sheath: Aramid
RAIDER 11 mm	EN 1891	CE	В	2600 daN(kg)	1900 daN(kg)	2200 daN(kg)	8	4,7 kN	3,3%	0,6%	81 g	41 %	59 %	0,5%	Sheath: Aramid
RAIDER TACTIC 11 mm	EN 1891	CE	A	2400 daN(kg)	1800 daN(kg)	2200 daN(kg)	6	5,9 kN	3,2%	0 %	75 g	30 %	70%	0,5 %	Sheath: Aramid Core: Polyamide
SEMI-STATIC INTERVENTION										1					
ACCESS 10,5 mm UNICORE	EN 1891	CE	A	3000 daN(kg)	1800 daN(kg)	2400 daN(kg)	12	5,3 kN	3 %	0 %	65 g	38 %	62 %	2,5%	Polyamide
INTERVENTION 9mm	EN 1891	CE	B	2100 daN(kg)	1350 daN(kg)	-	8	4 kN	3,6%	0,3%	51 g	43 %	57%	4%	Polyamide
INTERVENTION 10mm	EN 1891	CE CE	A	2500 daN(kg)	1800 daN(kg)		5	5,3 KN	4,4%	0%	62g	43%	5/%	4%	Polyamide
	EN 1891	CE	A	3400 daN(kg)	1050 daN(Kg)	2400 daN(Kg)	12	5,5KN	5 % 2 10/-	0,8%	05g	38 % 36 %	02 % 6/1 0/-	5 % 1 10/-	Polyamide
INTERVENTION 11.5mm	EN 1891	CF	A	3500 daN(kg)	2200 daN(kg)	2400 daN(kg) 2600 daN(kn)	> 20	5.6 kN	2,1 /0	0.5 %	74y 78a	38%	62 %	5%	Polyamide
DYNAMIC ROPES				(ng)				.,=	_, , , , ,	-,-,0		3	,0	- /*	
TOP GUN II 10,5 mm UNICORE	EN 892	CE	0	2100 daN(kg)	-	1700 daN(kg)	Factor 2	-	-	-	68 g	40%	60%	-	Polyamide
SOFT FAST ROPE 40 mm	-	-	-	7600 daN(kg)	-	-	-	-	-	-	94 kg /100 m	-	-	-	Polyamide
TEXTURIZED FAST ROPE 44 mm	-	-	-	Polyamide sling termination: 6000 kg Metal termination: 3000 kg	-	-	-	-	-	-	96 kg / 100 m	-	-	-	Polyamide
Clanderd	FN 1201	-	Type A	>2200 daN(kg)	>1500 daN(kg)	>1500 daN(kg)	> 5/100 kg	< 6kN	$\leq 5 \%$	20mm+10 (D-9mm)	-	-	-	-	
reference	LIN 1031		Туре В	>1800 daN(kg)	>1200 daN(kg)	>1200 daN(kg)	> 5/80 kg	< 6kN	≤ 5 %	< 15 mm	-	-	-	-	

<**₿**> 14



Multi-use: BEAL accessory cords from 4 to 8 mm in diameter conform to the requirements of the UIAA and European Standards.



40 / 60 / 80 / 100 / 120 / 150 cm

60 / 120 / 180 cm

240 cm

60 cm = 48 a

60 cm = 19.8 a

240 cm = 79 a

2200 daN (kg)

2200 daN (kg)

2200 daN (kg)

Polvamide

Dvneema

Dvneema

5

4

4

CE

≤ß>

Dyneema Flats

18 mm

10 mm

10 mm

EN 795B

EN 354 EN 566

EN 7958

CE/UIAA

CE/UIAA

ESCAPER EN 795B

Detachable anchor system. The ESCAPER allows you to use a single length of rope and to rappel it from remove locations. It can be used with all rope diameters, the limits being imposed by the braking device that is used with the rope. It works with rope lengths up to 80m. The length can be limited by the friction of the rope. To retrieve the ESCAPER, pull then / release the rope. It takes an average of 8 consecutive pull/release motions to detach and retrieve the ESCAPER.

STRONG POINTS:

- Extremely safe, it only requires a tension of 10 kg to avoid the locking system from sliding.
- A total loosening of the tension on the rope generates a sliding of a few centimeters.
- A sliding of at least 50 cm is necessary to detach the system.
- Very light: made of rope, webbing and bungee band (100 % textile).

CE x 8 Ref: BLESC

Weight	Resistance	Particularity
90 g	18 kN	The bungee band allowing the system work may be replaced. Patented.

ANCHOR STROP EN 795B

Semi-temporary anchor made from 7 mm galvanised steel cable with plastic cover and 2 swaged terminations.

STRONG POINTS:

- Available in 0.5 m and 1 m lenghts.
- Allows making of semi-temporary anchors.
- Strength 2500 kg.
- Weight: 50 cm = 260 g 1 m = 434 g.

Ref 50 cm : BMANCH.050 Ref 1m : BMANCH.100



CE

wear indicator

Ref 80 cm : BSL.80

Ref 120 cm : BSL.120

Ref 150 cm : BSL.150

DYNALOOP EN 566, EN 354



A dynamic rope sling for work restraint. The dynamic characteristics of this sling are far superior to those of a traditional static lanyard or webbing sling.

STRONG POINTS:

150 cm / 135 g

- Perfectly adapted for work positioning at height.
- The use of a dynamic rope can improve the level of safety.

120 cm / 105 q

- Sewn termination protected by a heat shrink
- cover. • Breaking load 2200 daN
- Marked with a unique serial number

60 cm / 55 g

Ref: BLDL.60

Ref: BLDL.120

Ref BIDI 150



EYE LOOP EN 795B. EN 354

A heavy duty tubular webbing

ABSORB'AIR EN 355

Webbing construction energy absorber. Energy is absorbed through the controlled tearing of the webbing's weft during deployment

STRONG POINTS

- Compact and lightweight.
- Easy to open semi-rigid pouch.
 Easy to inspect in its entirety.
- Easy to dry once unrolled.
- Can be combined with a DYNAPRO lanyard to create a lanyard with energy absorber.
- · Marked with a unique serial number and labelled to accommodate personal markings as well as a QR code to assist traceability.



Fall arrest lanyard with integrated energy absorber (EN355 + EN 362) designed for work environments with a fall risk.

STRONG POINTS

- ABSORB'AIR absorber combined with DYNAPRO lanyard.
- Supplied with an AIR-HOOK LARGE connector to connect to the anchor point and an O'LIGHT 3-MATIC connector to connect to the harness.
- Sewn terminations with reinforced eyes to protect the rope
- Removable cover allows the inspection of termination stitches
- Marked with a unique serial number and equipped with a label to accommodate personal markings as well as a QR code to assist traceability.

140 cm

• Available in 3 lengths (including connectors and absorber): 1m / 1.5m / 2m.



DYNAPRO-AIR V HOOK EN 355 / EN 362

V-shaped fall arrest lanyard with integrated energy absorber (EN355 + EN362). Designed as a progression lanyard for work environments with a fall risk, it is well adapted to structures where anchor points are cables, bars or beams.

- ABSORB'AIR absorber combined with a V-shaped lanyard.
- · V-shaped lanyard with two symmetrical rope legs for progression
- using fall arrest techniques. Supplied with 2 AIR-HOOK LARGE connectors to clip anchor points and an O'LIGHT 3-MATIC connector to connect to the harness.
- · Sewn terminations with reinforced eyes to protect the rope
- 2 removable covers allow the inspection of termination stitches
- Marked with a unique serial number and equipped with a label to accommodate personal markings as well as a QR code to assist Available in 2 lengths (including connectors and absorber): 1m / 1.5m



DYNAPRO-AIR V HOOK XL EN 355 / EN 362

V-shaped fall arrest lanyard with integrated energy absorber (EN355 + EN 362). Designed as a progression lanyard for work environments with a fall risk, the size of its connectors make it particularly suited to metal structures.

STRONG POINTS

- ABSORB'AIR absorber combined with a V-shaped lanyard.
 V-shaped lanyard with two symmetrical rope legs for progression using fall arrest techniques. Its 2 two metre legs allow fluid progression on large structures
- Supplied with 2 AIR-HOOK XL connectors that can clip anchors on large structures as well as an O'LIGHT 3-MATIC connector to connect to the harness
- Sewn terminations with reinforced eyes to protect the rope.
 2 removable covers allow the inspection of termination stitches.
- Marked with a unique serial number and equipped with a label to accommodate personal markings as well as a QR code to assist traceability.
 - Available in 1 length (including connector and absorber): 2 m.



DYNAMIC LANYARDS

DYNAPRO EN 354 / EN 795B



Simple dynamic rope lanyard with sewn termination for work restraint. The dynamic characteristics of this lanyard are far superior to those of a traditional static lanyard.

STRONG POINTS

- Perfectly adapted for work positioning at height.
 Sewn termination with reinforced eye to protect the rope as well as a
- Removable cover allows the inspection of termination stitches.
 Marked with a unique serial number and labelled to accommodate personal markings as well as a QR code to assist traceability.
- PINCH to assist connector orientation. · Enhanced level of protection thanks to the use of a dynamic rope
- **أمر** 140 g 0.6 m ᆆ 170 g Stitching protected by a moulded cover 1 m <u>أ</u> 200 g 1.5 m Strength: 2200 daN (kg) Ref: BLD



Adjustable, dynamic rope lanyard with sewn terminations. The dynamic performance of this lanyard is greatly superior to that of traditional static lanyards. By making your own double fig-8 knot point of attachment to your harness you can obtain an assymetric 'V' lanyard adjusted to your needs. The lanyard thus made, in conformity with the notice, meets Standard EN 354.

STRONG POINTS

- Possible to clip long or short.
 Ability to pass intermediate anchors thanks to the 2 branches.
- · Sewn terminations fitted with a sleeve to protect the rope and a pinch to hold the karabiner in position.
- Improved security in the event of a fall (even of high factor) on the lanyard because of the use of dynamic rope.
- · Attach with a maillon rapide or directly onto the chest ring.



Assymetric 'V' dynamic rope lanyard with sewn terminations. The dynamic performance of this lanyard is greatly superior to that of traditional static lanyards.

STRONG POINTS

- Perfectly adapted to work at height and rescue.
- Ability to clip-in short or long.
 Ability to pass intermediate anchors thanks to the 2 branches.
- · Sewn terminations fitted with a sleeve to protect the rope and a
- pinch to hold the karabiner in position.
- Improved security in the event of a fall (even of high factor)on the lanyard because of the use of dynamic rope.
 Secure with a maillon rapide.
- Strength: 2200 daN (kg) شً 160 g 0.3m Stitching protected by a moulded cover 0.6m Ref: BLDPV.60 / BLDPV.100 / BLDPV.150

≤ß≥ 18

LANYARDS

NEXUS EN 354 / EN 795B

Single or double lanyard with sewn termination for restraint at the workstation or progression on a restraint lifeline. This versatile lanyard allows for temporary anchorages.

STRONG POINTS

- Perfectly suited for working at height. Stitched termination with PINCH to lock the carabiner at its end.
- The connection to the harness is done by a lark head. Marked with a unique serial number.



ADJUST'AIR EN 358

Adjustable (EN358) work positioning lanyard in 12.5mm semi-static rope.

STRONG POINTS

- Ergonomic, captive rope clamp.
- Available in 3 lengths: 2 m / 3 m / 5 m.
- Sewn termination with reinforced eye to protect the rope.
 Removable cover allows the inspection of termination stitches.
- Tubular protection webbing for the rope.
- Marked with a unique serial number and labelled to accommodate personal markings as well as a QR code to assist traceability.



System for securing the karabiner at the end of a rope or tape lanyard. Made out of particularly strong material, it ensures effective protection against abrasion when in contact with the rock.







Œ



HERO PRO EN 361 / EN 358 / EN 813

A fall arrest and work positioning harness.

STRONG POINTS

- X shaped shoulder straps increase comfort and ensure excellent load distribution.
- The padded shoulder straps are held apart to minimize neck chafing.
- The waist belt, leg loops and shoulder straps are lined with breathable foam to improve comfort and to reduce perspiration.
- The waist belt's two lateral attachment loops can be folded back to minimise hindrance.
- The dorsal attachment point is made from steel.
 Two opening quick release buckles (one per leg loop) enable the harness to be easily fitted even with cumbersome footwear.
- 4 large, pre-shaped gear loops are positioned around the waist belt to easily accommodate all equipment.
- Mini gear loops compatible with item of the WorkStation.



Size	Weight (g)	Waist belt (cm)	Leg loop (cm)	Torso circumference (cm)	Stature (cm)	Chest height (cm)
S	2065	70-90	50-65	70-100	155-175	55-70
M-L	2125	80-105	55-65	80-120	170-185	65-80
XL	2230	90-130	60-70	100-140	180-210	75-85

HERO PRO HOLD UP EN 567 : 2013 Ø 8-13mm / EN 12841 : 2006-B Ø 10-13mm 100kg - EN 361 / EN 358 / EN 813



A fall arrest and work positioning harness with ascender to aid rope ascents.

The harness is equipped with the HOLD UP compact chest ascender that is optimised for ascending ropes. The HOLD UP is designed to stay parallel to the user's body allowing the rope to slide easily through the device, making it particularly user friendly.

STRONG POINTS

- X shaped shoulder straps increase comfort and ensure excellent load distribution
- The padded shoulder straps are held apart to minimise neck chafing.
- The waist belt's two lateral attachment loops can be folded back to minimise hindrance
- The dorsal attachment point is made from steel.
- Two opening quick release buckles (one per leg loop) enable the harness to be easily fitted even with cumbersome footwear.
- A FLAT LINK connector allows the shoulders straps to be easily connected to the lower part of the harness and is compatible with the HOLD UP chest ascender. Its flat working surface ensures the webbing is properly seated.
- 4 large, pre-shaped gear loops are positioned around the waist belt to easily accommodate equipment.
- Mini gear loops compatible with item of the WorkStation.



Size	Weight (g)	Waist belt (cm)	Leg loop (cm)	Torso circumference (cm)	Stature (cm)	Chest height (cm)
S	2065	70-90	50-65	70-100	155-175	55-70
M-L	2125	80-105	55-65	80-120	170-185	65-80
XL	2230	90-130	60-70	100-140	180-210	75-85

<ß>

OFF SHORE EN 361 / EN 358 / EN 813

Integral suspension harness with metal parts made of stainless steel. This harness is equipped with a sternal fall arresting point (EN361), two lateral points (EN358) and a ventral point (EN813) made of textile.

STRONG POINTS

- Textile suspension point which allows a great freedom of movement.
- Quick release stainless steel thigh leg loop buckle for fast fitting.
- 4 organiser gear loops to the belt.
 2 connector book loops to the shoulders
- 2 connector hook loops to the shoulders.
 A knife holder on the shoulder.
- Traceability: identification area with QR code to create your own identification.
- Mini organiser gear loops for hanging WorkStation accessories.
- The shoulder strap slides in the sternal ring allowing easy donning.



Size	Weight (g)	Waist belt (cm)	Leg loop (cm)	Stature (cm)
1 (S-M)	1920	70-105	50-65	160-180
2 (L-XL)	2080	85-130	60-75	175-210

HOOK BUCKLE



HARNESS

Ref S : BHPSH.1 M-L : BHPSH.2 XL : BHPSH.3

SHAOLIN EN 358 / EN 813/ (EN361 With a torso)

A lightweight fall arrest and work positioning harness.

STRONG POINTS

- This harness benefits from new technology in the PRO range: WEB CORE technology provides exceptional levels of comfort thanks to optimal pressure distribution on hips and thighs. WEB CORE is a wide, thin and lightweight piece of webbing laser cut to the shape of the harness. This results in a more compact, lightweight and above all more comfortable harness.
- Its ergonomic construction allows a large range of movement.
 The low position of the ventral attachment point yields maximum progression when ascending ropes, whilst its large diameter provides the space for multiple connection to be made i.e. ascenders, connectors, descender and lanyards.
- Two ways of attaching equipment: A large ring provides the space for multiple karabiners and lanyards to be connected and accessed easily during a rescue.
- Two textile attachment points for connecting lanyards metallic devices on both sides of the ring.
- 2 lateral attachment points EN 358
- 1 dorsal attachment point for winching. • A handle can be fitted at the back for rescue use.
- 5 gear organisers, 4 gear loops and 6 fabric loops to connect parts of the WORK STATION range.
- Replaceable rear elastics on leg loops.
- Traceability via an identification area with QR code which allows a personal identifier to be generated (your name and unique ID).
- · Compatible with the AIR TOP and YPSILON chest harness to create a full body harness EN 361.

USES

Work at height, rescue, route setting, and high ropes course technicians.

Size	Weight (g)	Waist circumference (cm)	Leg loop circumference (cm)
S	700	60-100	42-60
M-L	760	72-120	52-70
XL	810	85-140	57-75

HERO SIT EN 358 / EN 813 / (EN361 With a torso)

Work positioning and rope access harness.

STRONG POINTS

S

M-L

XL

- The semi-rigid leg loops and waist belt assure optimal pressure distribution where the body is in contact with the harness.
- The waist belt and leg loops are lined with a breathable foam, increasing comfort and reducing perspiration.
- •The waist belt's two lateral attachment loops are articulated to minimise hindrance.
- Two double action opening quick release buckles (one per leg loop) enable the harness to be easily fitted even with cumbersome footwear.
- The rear of the waist belt contains an area to allow personal marking such as your company's name in addition to a QR code which allows a true identifier to be generated (your name and unique ID).
- 3 large, pre-shaped gear loops are positioned around the waist belt to easily accommodate all equipment.
- 4 mini gear loops can be used to attach 'AIR-LEASH' extendable tool holders or 2 'TOOL-BUCKET' tool pouches.

Weight (g)

1437

1478

1568

Waist circumf

(cm)

70-90

80-105

90-130

Leg loop circui

50-65

55-65

60-70



CE

SHAOLIN

+ AIR TOP

SHAOLIN

+ YPSII ON

Ref S : BHPHS.1 M-L : BHPHS.2 XL : BHPHS.3



≤ß≥

AIR TOP EN 361 / EN 12 277 type D

Adjustable chest harness with figure of 8 shape for use with a HERO SIT or SHAOLIN sit harness. This comfortable harness ensures the user remains in an upright position during a fall.

STRONG POINTS

- Figure of 8 shape provides freedom of movement and distributes pressure around the chest evenly.
- 2 adjustment buckles to adjust the length of the shoulder straps.
- A single adjustment buckle allows the sternal attachment point to be correctly positioned in relation to the user, regardless of their physique.
- A reinforced webbing fall arrest attachment point is ideal in confined spaces allowing progression without hindrance
- Can easily be fitted with an elastic positioning strap for the chest ascender.
- Large elastic retainers help tidy the chest ascender's webbing.

USES

Work at height, industry, rescue, route setting

	Weigin (g)	(cm)	
Size	Weight (g)	Waist circumference	

YPSILON EN 361

Lightweight and adjustable Y-shaped chest harness compatible with HERO SIT and SHAOLIN sit harnesses. Comfortable and easy to fit, it ensures the user remains in an upright position during a fall.

STRONG POINTS

- Lightweight
- Adjustments are made using a front buckle at shoulder height and a dorsal rear buckle.
- The shoulder strap slides through the sternal D-ring which provides a large range of movement and ensures ease of fitting.
 A slight narrowing of the shoulder straps prevents chafing around the neck.
- Multiple attachment points for the elasticated chest ascender retainer. • Two reinforced loops per shoulder strap can be used to attach scaffolding hooks.

USES

Work at height, industry, rescue

one size	370	(cm) 60-140
Size	Weight (g)	Waist circumference

AIR SIT

Stable and comfortable suspended work seat for rope access.

STRONG POINTS

- Triangulation of the 2 lateral attachment points assists stability.
- Durable and breathable comfort padding.
 2 plastic lateral gear loops are pre-shaped for ease of clipping.
- 4 mini gear loops are equally available on the sides to attach 'AIR-LEASH' extendable tool holders or 2 'TOOL-BUCKET' tool pouches.
 A ring under the seat can be used to attach a bag.

Weight (g)	
1365	50 x28x12





CE

AIR TOP + SHAOLIN



HARNESS







STYX FAST EN 361

A very light and compact fall arrest harness with 2 connection points : 1 sternal and 1 dorsal. Quick release buckles to the thighs and a foamed back allow a quick sitting. Versatile because it can be combined with a work position belt.

STRONG POINTS

- Foamed shoulder and back straps for comfort and easy donning. Quick release buckles to the leg loops allows quick fitting.
- Possibility of adding a work position belt EN358: STYXBELT.
- Straps with protection to avoid rubbing at the neck. 2 organiser gear loops to the hips.
- 2 connector hook loops to the shoulders.
- Differentiation in color between left and right parts to facilitate the setting up.
- 2 mini organiser gear loops to attach WORKSTATION accessories.



Size	Weight (g)	Leg loop (cm)	Chest height (cm)	Torso circumference (cm)	Stature (cm)
U	1255	40-80	55-80	80-140	160-195

SYNCRO EN 358 / EN 361

Particularly lightweight work positioning and fall arrest harness adapted specifically for industrial and energy related work environments.

STRONG POINTS

- X shaped shoulder straps increase comfort and ensure excellent load distribution.
- The padded shoulder straps with well-placed retainers minimise neck chafing.
- Two double action opening quick release buckles (one per leg loop) enable the harness to be easily fitted even with cumbersome footwear.
- Both the lateral and dorsal attachment points consist of sewn rope rings to reduce weight, noise and damage to delicate surfaces or coatings, particularly when ascending inside a wind turbine's tower.
- The rear attachment point consists of a sewn rope ring to reduce weight and noise. Its red colour promotes efficient identification in emergencies.
- The sternal webbing strap with fall arrest attachment point can be easily opened and closed to assist harness fitting.
- The rear of the waist belt contains an area to allow personal marking such as your company's name in addition to a QR code which allows a true identifier to be generated (your name and unique ID).
- · 2 fixed loops on the shoulder straps allow the attachment of an accessory like a radio or storage of scaffolding hooks. 4 large, pre-shaped gear loops are positioned around the waist
- belt to easily accommodate all equipment.
- 6 mini gear loops can be used to attach 'AIR-LEASH' extendable tool holders or 3 'TOOL-BUCKET', 'LONG TOOL BUCKET' or 'GLASS BUCKET' tool pouches.



Size	Weight (g)	Waist belt (cm)	Leg loop (cm)	Torso circumference (cm)	Stature (cm)	Chest height (cm)
1 (S-M-L)	1700	65-105	45-65	80-120	160-180	55-75
2 (L-XL)	1750	100-130	60-75	90-140	175-210	65-85

LIFE JACKET

STYX BELT EN 358

Workstation belt. This adjustable belt makes it possible to adjust positioning rings to all morphologies or all situations by a simple sliding. The quick-release buckle offers a simple opening / closing. The belt is compatible with the STYXFAST harness.

STRONG POINTS

- Two adjustable aluminum side rings.
- A wide foamed belt for maximum comfort. A quick buckle at the belt.
- A large organiser gear loop.
- Traceability: identification area with QR code to create your own . identification.
- 6 mini organiser gear loops to attach WORKSTATION accessories. .







STYX RESCUE / STYX RESCUE JACKET EN 361

Lightweight and compact fall arrest harness with two attachment points: 1 sternal and 1 dorsal.

STRONG POINTS

- Different coloured leg loops help distinguish them from the shoulder
 straps and so accelerate fitting.
- The dorsal section contains an area to allow personal marking such as your company's name in addition to a QR code which allows a true identifier to be generated (your name and unique ID).

WITH JACKET

• The dorsal section contains an area to allow personal marking such as your company's name in addition to a QR code which allows a true identifier to be generated (your name and unique ID).

Size	Weight (g)	Leg loop (cm)	Chest height (cm)	lorso circumference (cm)	Stature (cm)
U	1062	40-80	55-80	80-140	160-195

CE Ref. BHPSTR . Ref. BHPSTJR

TRI-ANGEL EN 1497 : 2007 / EN 1498 : 2006

Evacuation triangle for vertical rescues.

STRONG POINTS

- Straightforward positioning using 2 adjustable straps.
- The straps, which are a different colour to the rest of the triangle, assist with both the ease and speed of deployment of the TRI-ANGEL onto the casualty.
- The TRI-ANGEL adjusts in size to match the casualty using a webbing positioning scale with 3 settings.
- Marked with a unique serial number.
- · Includes an area to allow personal marking such as your company's name in addition to a QR code which allows a true identifier to be generated (your name and unique ID).

Weight: 747 g



CE

15-25 daN

weight (g)

390

Electrical insulation

Open chinstrap between 15 daN and 25 daN

SKYFALL EN 397 / EN 50365

Ultra-light helmet in ABS material with internal suspended harness and polystyrene reinforcement for optimal energy absorption in case of impact.

STRONG POINTS

- Micro adjustable thanks to a precise adjustment dial.
- Adjustable chinstrap with Quick-release buckle.
- 4 Headlamp clips are integrated into the shell.
- Slots for ear protector fixing.
- Internal comfort padding is removable and machine washable.
- Security device release system between 15 and 25 daN in order to avoid strangulation.







Circomference mini (cm)

54

HIGH VISIBILITY



CE

CE

Lateral deformation

Molten metal splach

Temperature low resistance (-40°C)

Circomference maxi (cm)

62

SKY VISOR EN 166



Compatible with SKYFALL

size	weight	Material	Dimensions
small	60 g	polycarbonate	200 mm - 146 mm- 96 mm

-BERLS
Ref. BKPSV.S

		ROTECTO	PRC S VENUAR	HECTRON	ABURION CONSIGNATION OF TANK	Renterins of the constraints	overstoph Market	and the second second	AUON
	EN 397	EN 12492	EN 12492	EN50365	15-25 daN	EN 12492	EN 397	EN 397	Temperature mini-maxi
SKYFALL EN 397		-	-			-			-40°C / +50°C
MERCURY EN 12492	-			-	-		-	-	-20°C / +35°C
MERCURY Group EN 12492	-			-	-		-	-	-20°C / +35°C

<<mark>ß</mark>>

MERCURY EN 12492

Hybrid helmet featuring an ABS shell with a polystyrene liner.



POINTS FORTS

- Micro-adjustable thanks to a precise adjustment dial.
- Large volume of the hull for optimum comfort and protection.
- Very good ventilation. 4 hooks to attach a headlamp are integrated into the helmet.
- Lateral perforations for fixation of hearing protection.
- Resistance of the chinstrap to 50 daN to avoid the loss of the helmet in case of shock.
- A magnetic closure of the chinstrap buckle for easy positioning and release even with gloves and one hand.

50 daN

ñ

• Removable and machine washable internal comfort foams.



MERCURY GROUP EN 12492

A robust helmet with an ABS outer shell, designed for intensive use in a group environment such as on high ropes courses. The inner liner is suspended and easily adjustable with a strong and simple buckle. The helmet is designed to be durable and easy to wash.

POINTS FORTS

- Robustness
- Easy to wash inner liner
- Customization on demand



> Ear defender adaptor with bayonet system

> Compatible with MERCURY helmets



E

Major Axis Strend

22 kN

Open Gate Streng

6 kN

Ref. BMCLOL

Maior Axis Stre

22 kN

Open Gate Streng

8 kN

Major Axis Streng

26 kN

Open Gate Strength

7 kN

Major Axis Streng

26 kN

Open Gate Strengt

7 kN

Ref. BMCLBLN

Ref. BMCLOU3

C E

Minor Axis Strength

8 k N

Weight

74 q

Minor Axis Strength

8 k N

Weigh

82 g

Minor Axis Strength

8 kN

65 g

Minor Axis Strength

8 kN

65 g

F (UIAA)

(LIAA)

E

(ULAA)

(ULAA)

O'LIGHT EN 362:2004 /B - EN 12275:2013®

Symmetrical aluminium oval shaped connector for use with equipment with swivelling side plates such as pulleys, rope clamps, mobile fall arrest devices, etc...

STRONG POINTS

- Screw lock system.
- Individual serial number.
- Keylock system.

O'LIGHT 3-MATIC EN 362:2004 /B - EN 12275:2013®

Symmetrical aluminium oval shaped connector for use with equipment with swivelling side plates such as pulleys, rope clamps, mobile fall arrest devices, etc...

STRONG POINTS

- Triple action 3-MATIC locking system.
- Individual serial number.
- Keylock system.

BE LINK EN 362:2004 /B - EN 12275:2013®

Asymmetrical aluminium connector for lanyards or for use with belay devices. The asymmetrical shape helps to guide the device towards the connector's apex.

STRONG POINTS

- Screw lock system
- Individual serial number.
- Keylock system.

BE LINK 3-MATIC EN 362:2004 /B - EN 12275:2013®

Asymmetrical aluminium connector for lanyards or for use with belay devices. The asymmetrical shape helps to guide the device towards the connector's apex

STRONG POINTS

- Triple action 3-MATIC locking system. Individual serial number.
- Keylock system.

BE LOCK EN 362:2004 /B - EN 12275:2013®

Symmetrical aluminium screw gate connector with large capacity and opening to accommodate multiple items. Its generous loading surface and HMS shape facilitate its use with Clove and Italian hitches.

STRONG POINTS

- Screw lock system.
- Individual serial number.
- Keylock system.

BE LOCK 3-MATIC EN 362:2004 /B - EN 12275:2013®

Symmetrical aluminium screw gate connector with large capacity and opening to accommodate multiple items. Its generous loading surface and HMS shape facilitate its use with Clove and Italian hitches.

STRONG POINTS

- Triple action 3-MATIC locking system.
- Individual serial number.
- Keylock system.

FLAT LINK EN 362:2004/B

Symmetrical, trapezoidal shaped aluminium karabiner designed to connect the top and bottom parts of a full body harness. Its flat working surface ensures the webbing is properly seated. The FLAT LINK was designed to be compatible with the HOLD UP chest ascender

STRONG POINTS

- Double action locking gate
- Individual serial number.
- Keylock nose.







Major Axis Strength	Minor Axis Strength
26 kN	8 kN
Open Gate Strength	Weight
8 kN	100 g





	-
20 kN	10 kN
Open Gate Strength	Weight
5 kN	81 g

















28

≤ß≥







LOCKING CONNECTOR

O'SMITH EN 362:2004 /B,A,T - EN 12275:2013®

Symmetrical oval shaped steel connector.

STRONG POINTS

- Screw lock system. • Individual serial number.
- Keylock system.



O'SMITH 3-MATIC EN 362:2004 /B,A,T - EN 12275:2013

Symmetrical oval shaped steel connector.

STRONG POINTS

• Triple action 3-MATIC locking system.

with connections to metal anchors

AIR-SMITH EN 362:2004B, A, T / EN 12275®

Its capacity allows it to accommodate multiple items

- Individual serial number.
- Keylock system.





Major Axis Strength

52 kN

Open Gate Strength

18 kN

Major Axis Streng

52 kN

Open Gate Strength

18 kN

Maior Axis Strena 22 kN

Weight

475 g

Ref. BMCLAS

D

D

Maior Axis Stren

0

Maior Axis Strenat

30 k N

Open Gate Streng

8 kN

Ref. BMCLOS



CE

Minor Axis Strength

16 kN

Weight

251 g

Minor Axis Strength

16 kN

Weight

251 g

CE

C E

CE

Minor Axis Strength

16 kN

Weight

179 g

C E 

METAL

STRONG POINTS

- Screw lock system.
- Individual serial number. Keylock system.

AIR-SMITH 3-MATIC EN 362:2004/B, A, T / EN 12275®

High capacity asymmetrical steel connector with large opening to assist with connections to metal anchors Its capacity allows it to accommodate multiple items.

High capacity asymmetrical steel connector with large opening to assist

STRONG POINTS

- Triple action 3-MATIC locking system. Individual serial number.
- Keylock system.



AIR-HOOK LARGE EN 362:2004/A

Auto-locking aluminium connector with large opening. Ideal for connections to cables, bars and beams.

STRONG POINTS

- Ergonomic lock- unlocking trigger.
- Individual serial number.

AIR-HOOK XL EN 362:2004/A-T

Auto-locking aluminium connector with very large opening. Ideal for connections to cables, bars and beams.

STRONG POINTS

- Ergonomic lock- unlocking trigger.
 Individual serial number.

Name	Working load limit	Breaking load (Kg)	Weight	lenght	width	opening
STANDARD GALVA 8 mm	700	3500	77 g	73 mm	34mm	11,4 mm
STANDARD GALVA 10 mm	1100	5500	137 g	88 mm	41,5 mm	12mm
IONG OPENING GALVA 7 mm	500	2500	60 g	78,5 mm	31 mm	16 mm
PEAR GALVA 10 mm	720	3600	185 g	118mm	65 mm	20 mm
5 DELTA GALVA 8 mm	550	2750	88 g	73 mm	56 mm	11 mm
DELTA GALVA 10 mm	990	4500	153 g	87 mm	66 m m	12mm
MAILLON SEMI CIRCULAR 10 mm	990	4500	153 g	86 m m	65mm	10 mm
Imaillon Delta Twist	600	3000	135 g	93 mm	62 mm	12mm











LOCKING CONNECTOR TWIN GATE

Twin Gate is a revolutionary concept for locking a karabiner, patented by Grivel/Simond It is incredibly simple and can be worked using just one hand. Unintentional opening is nearly impossible. In addition, the locking mechanism cannot become jammed. 2 versions are available:

• A solid and wire gate combination which open in opposite directions. •Two solid gates which open in opposite directions.

USE Ideal for use with a belay device

towards their correct position at

or lanyard which are guided

the karabiner's apex.

Belaying and abseiling

TWIN AUTO BELAY EN 362:2004 /B - EN 12275:2013®

Compact asymmetrical locking karabiner for use with a lanyard or belay device. Features the Twin-Gate concept with a second wire gate

STRONG POINTS

- TWIN GATE Concept
- High strength
 KEYLOCK nose system
- Excellent balance between

strength and weight

TWIN BELAY D EN 362:2004 /B - EN 12275:2013

Versatile mid-sized, asymmetrical HMS karabiner for use with single, half or twin ropes.

USE

Features the Twin-Gate concept with second wire gate.

STRONG POINTS

TWIN GATE Concept

- High strength
- KEYLOCK nose system

TWIN BELAY PEAR EN 362:2004 /B - EN 12275:2013®

Versatile mid-sized, symmetrical HMS karabiner for us with single, half or twin ropes. Features the Twin-Gate concept with two gates that open in opposite directions

USE

STRONG POINTS

Belaying and abseiling

- TWIN GATE Concept High strength
- KEYLOCK nose system

TWIN O EN 362:2004 /B - EN 12275:2013®

An oval automatic locking karabiner designed for use with equipment with swivelling side plates such as pulleys and descenders. The TWIN O is equipped with the TWIN-GATE concept and its two opposing gates. The absence of a traditional locking barrel reduces the potential of the karabiner becoming incorrectly positioned.

USE

STRONG POINTS

- TWIN GATE Concept
- High strength
- KEYLOCK nose system

TWIN GUIDE EN 362:2004 /B - EN 12275:2013®

A unidirectional automatic locking karabiner. An internal wire gate prevents the karabiner from becoming inverted and means the load remains well positioned along the long axis, for example at the end of a lanyard. The TWIN GUIDE is equipped with the TWIN-GATE concept and its two opposing gates. The absence of a traditional locking barrel reduces the potential of the karabiner becoming incorrectly positioned.

STRONG POINTS

• TWIN GATE Concept • High strength

• KEYLOCK nose system

Pulleys and pulley systems

TWIN SMITH CAPTIVE EN 362:2004 /B - EN 12275:2013®

A large capacity and high strength (45kN) asymmetrical steel locking karabiner. The TWIN SMITH CAPTIVE features the TWIN-GATE concept with a second wire gate that opens in the opposite direction.

STRONG POINTS

• TWIN GATE Concept • High strength

KEYLOCK nose system

USE Particularly suited to clipping into anchors and fixed lines, or for arborist work restraint. Its removable captive bar holds the TWIN SMITH CAPTIVE in place on equipment it is clipped into.





9 kN

Ref. BMCTBD



69 g



SYNNETRICALL TWIN GA	
Major Axis Strength	Minor Axis Strength
29 kN	10 kN
Open Gate Strength	Weight
10 kN	83 g
Rof RMCTRP	

ηση 🔊 🖸 ϵ



000 2 🔊 🕻

Major Axis Strength	Minor Axis Strength
24 kN	9 kN
Open Gate Strength	Weight
8 kN	86 g





Ref. BMTCG

Ref. BMTCO







Ref. BMCTSC

17 kN



≤ß≥



(LILAA)



PULLEY

 (\mathbf{B})

TRANSF'AIR 1 EN 12278

Large single pulley with swivelling side plate. Stainless steel axle and washer. The sheave is mounted onto a bronze collar to promote a good level of efficiency. Maximum Ø ≤ 16 mm. EN12278: 1998.

STRONG POINTS

- Unique number.
- High maximum working load.

TRANSF'AIR 1B EN 12278

Highly efficient single pulley with swivelling side plate and ball bearing mounted sheave. Its swivelling action allows the pulley to be positioned anywhere along the rope, whilst the ball bearings ensure maximum efficiency and durability. Ideal for intensive use with large rope diameters. Stainless steel axle and washers.

STRONG POINTS

- Ball bearings.
- Individual serial number.
- Swivelling side plate.
- USE Intensive use in load transfers or pulley systems.

TRANSF'AIR 2 EN 12278

Large double pulley with swivelling side plate well suited for use in pulley systems. Stainless steel axle and washer. The sheave is mounted onto a bronze collar to promote a good level of efficiency. Maximum $\emptyset \le 16$ mm. EN12278: 1998.

STRONG POINTS

 Unique number Swivelling side plate.

TRANSF'AIR 2B EN 12278

Highly efficient double pulley with swivelling side plates thanks to a ball bearing mounted sheave. Its swivelling action allows the pulley to be positioned anywhere along the rope, whilst the ball bearings ensure maximum efficiency and durability. Ideal for intensive use with large ropes diameters. Stainless steel axle and washers.

STRONG POINTS

- Ball bearings
- Individual serial number Swivelling side plate

USE

Intensive use in load transfers or pulley systems

TRANSF'AIR FIXE EN 12278

Compact and lightweight pulley with fixed side plates. Stainless steel axle and washer. The sheave is mounted onto a bronze collar to promote a good level of efficiency. Maximum $\emptyset \le 12$ mm. EN12278: 2007.

STRONG POINTS

- Unique number.
- Lightweight.

TRANSF'AIR FIXE B EN 12278

Pulley with fixed side plates and ball bearings for optimal efficiency. Its compact and lightweight nature make it easy to handle. Allows a pulley system to be set up by adding a component such as an ascender. Maximum \emptyset max \leq 13 mm. EN12278: 1998

STRONG POINTS

• Unique number. Ball bearings.



0

MBS 30 kN

max 16 mm

Ref. BMP1

Ref. BMP1B







METAL









MBS 20 kN









≤ß≥ 31



Ref. BMP2

Ref. BMP2E

max 12 mm

Ref. BMPF

Ref. BMPFB

(**B**)

 (\mathbf{B})

max 16 mm MBS 30 kN



90 a





		6
	(6	<







PULLEY

(**B**)

TRANSF'AIR TWIN B EN 12278

A double pulley with two inline stainless steel sheaves mounted on ball bearings. The TRAINSF'AIR Twin B is specifically designed for intensive use on rope or wire zip lines.

STRONG POINTS

- Two stainless steel in-line sheaves increase stability.
- Ball bearings ensure consistent efficiency regardless of the user's weight.
- Can accommodate up to 3 karabiners.
- Individual serial number.

USE

Rope or wire zip lines







TRANSF'AIR MINI EN 12278

Compact and lightweight pulley with swivelling side plate. Stainless steel axle and washer. The sheave is mounted onto a bronze collar to promote a good level of efficiency. Maximum $\emptyset \le 11$ mm. EN12278: 1998.

STRONG POINTS

Unique number.
Swivelling side plate.





Ref. BMPMINI

Q

MBS 45 kN

WLL 9 kN

Ref. BMAP4

Weight

188 a



RIGGING PLATE AND SWIVEL

AIR-PORT 4

Aluminium rigging plate which can accommodate 4 connectors.

STRONG POINTS

• 20 mm holes allow connectors with

Aluminium rigging plate which can accommodate

• 20 mm holes allow connectors with locking barrels to be

- locking barrels to be inverted easily.
- Individual serial number.

AIR-PORT 8

8 connectors.

STRONG POINTS

inverted easily.

STRONG POINTS

• Ball Bearings.

• Individual serial number.

• Individual serial number.



23.5 mm

20 mm

 (\mathbf{B})

.

84 mm

Ý

< 82.5 mm >

A

mm

85,4

¥



CE

Weight

92 g

Maximum

23.5 mm

20 mm

TWIST'AIR B EN 354

Compact aluminium swivel with ball bearings to optimise performance even when loaded.

39 mm
× ×
(\bigcirc)
(\bigcirc)

MBS 45 kN

WII 9 kN

Ref. BMAP8

<mark>₿</mark> M	8 22kN	8	Ce
Compo	itible	Maximum	Weight

18 mm

88 a

MBS 22 kN

WII 4 kN

Ref. BMSW

CE 0321 EN354:2002
72

AIR STOP EN 341 / EN 12841

Auto-block descender with anti panic function for a single rope.

STRONG POINTS

- Maximum working load of 130 kg with 9 mm rope, and up to 200 kg with ropes from 10 to 12 mm.
 Anti-panic function with 2 blocking positions.
 The maximum authorised speed of descent is 2 m/s.
 Useable on a wide spread of rope diametres from 9 to 12 mm (EN12841-C).
 Long control lever for a more progressive feel.
 Rope can be inserted into device without unclipping it.
 Unique serial number.

- Unique serial number.



AIR FORCE 8

Classic, robust and easy to use belay device. It is compatible with a large range of rope diameters whether single, double or twin.

The friction can easily be varied whatever the condition of the ropes (frozen, wet, different diameters...).



CE

İdN

Ref. BMFAM

MONITOR EN 353-2 / EN 12841-A 100kg

Aluminium mobile fall arrest device with swivelling side plate.

STRONG POINTS

- Mobile fall arrest device with camming action. Cam function reduces abrasion to the rope when activated.
- Meets the requirements of the following standards: EN 353-2, EN 12841-A 100 Kg diameter 11-13 mm (EN1891).
 Rescue : maximum 200 kg, ø11-13 mm.
- Swivelling side plate allows for ease of installation on the rope.
 A lateral brake converts the MONITOR into a rope clamp for work positioning.
- Easily locks as a result of a fall.
 Easily follows the operator both during ascent and descent.
- Marked with a unique serial number.
- The MONITOR can be complimented with a MOBILE-LANYARD and its 2 attachment points.





MOBILE-LANYARD EN 354

Lanyard with 2 attachment points. The MOBILE-LANYARD is certified to work with the MONITOR mobile fall arrest device, enabling it to be positioned away from the operator.

Allows the operator to create a short or longer link dependant on their needs: Short link for work on a gentle slope or to limit the length of a fall (20 cm).

Longer link to distance the rope from the operator and to gain freedom of movement (40 cm).

STRONG POINTS

 Includes two PINCH's to ensure the correct orientation of the connector at its extremity.

Marked with a unique serial number.

Strength: 2200 daN (kg)

Weight: 64g



top top top top

Ś

Ś



FALL ARREST

• A length of rope 10 m / 15 m / 20 m / 30 m / 50 m / 60 m with a

• 11 mm diameter with sewn termination

If this diameter with second connector to attach
 1 BE-LOCK 3-MATIC connector to attach

Each length is represented by a colour for quick and efficient identification of both

the rope to the anchor point.

AIR-KIT 11 MM EN 353-2 et EN 12841-A 100 Kg



CE EN 567 : 2013, diameter 8-13mm CE EN 12841: 2006-B, diameter 10-13mm 100kg

Specific kit to create a mobile fall arrest system (EN 353-2 and EN12841-A 100 Kg) especially adapted to vertical work or work on inclined surfaces.

KIT INCLUDES

- A MONITOR mobile fall arrest device.
 A MOBILE-LANYARD with 2 positions: 20
- cm and 40 cm. 2 O'LIGHT 3-MATIC connectors to attach the lanyard to both the MONITOR and the harness.
- Connectors: two O'LIGHT 3-MATIC and one BE LOCK 3-MATIC.

STRONG POINTS

Weight: 498g

- Removable cover allows the inspection of termination stitches • Products marked with a unique serial number and equipped with a label to accommodate personal markings as well

as a QR code to assist traceability.

- 10 m and 30 m Orange. • 15 m and 50 m - Blue.
 - 20 m and 60 m Red.

its length and diameter:



20 m: BFAK11.20 60 m : BFAK11.60



 35

HANDS UP EN 567 : 2013, Ø8-13 mm - EN 12841: 2006-B, Ø10-13 mm 100 kg

Handled ascender with ergonomic design to aid rope ascents with one or two hands.

STRONG POINTS

- Can be used to compliment the HOLD UP chest ascender or any other ascender for rope ascents
 Large lower attachment hole easily accommodates the connector for the AIR STEP foot loop.
 The ascender's shape allows it to be held with two hands when
- ascending rope: one on the side beneath the trigger and one above it. • The handle is reinforced to improve ergonomics and comfort. • Large lower attachment hole can accommodate multiple
- karabiners and maillons. All-metal construction of the operating mechanism to increase
- durability
- An ergonomic protruding lever facilitates cam operation.

Weight: 265g



Ref. BMBHAR

CE



AIR-STEP

Adjustable footloop with quick adjusting system around the foot for ascending fixed ropes with an ascender.

STRONG POINTS

- Quick adjsuting system with ON / OFF function. In the ON position, the user's foot stays locked in the footloop. In the OFF position, the adjustment system does not engage, meaning the user's foot is not locked. • A large buckle facilitates adjustments of the footloop, even when wearing
- gloves. A stiffener in the loop helps to place a foot inside it.
- · Reinforced with webbing to help protect against abrasion.

USE

Gone back up on rope

Weight: 75 g





≤ß≥

HOLD UP EN 567 : 2013 Ø 8-13mm - EN 12841 : 2006-B Ø 10-13mm 100kg

A compact ventral ascender for ascending ropes

STRONG POINTS

- The attachment hole protrudes from the ascender's body at a 90 degree angle. This ensures the device remains both upright and parallel to the user's body and allows the rope to easily slide through the device.
 Positioned low on the harness to maximise progression with every move.
 All-metal construction of the operating mechanism to increase durability.

- An ergonomic protruding lever facilitates cam operation.
 Compatible with all PRO harnesses through the use of a FLAT LINK connector, which connects the harness to the ascender.

Weight: 90 g



TRACT UP EN 567 : 2013 Ø 8-13mm



STRONG POINTS

- Allows the recovery and the lifting of light loads
 Blocker of useful repair during laborers(operations) of mouflage and help
 In help: back up line glide in 250 kg

Compatibility = 8 in 11mm

Charge with maximal use in mode blocker: 2,5kN Breaking load in mode blocker: 4kN Materials: aluminum, stainless steel and silicone.

LIFE EXPECTANCY

Duration of storage = 5 years Operating life = 10 years

IT IN 567 + UIAA 126 Weight: 80 g









≤ß>

37

CE





COMBI PRO 40

Bag for professionals who require quick and easy access to their kit.

STRONG POINTS

- Benefits from BEAL's 'QUICK RELEASE' system to accelerate access to the bag's contents via two back panel sections. • Once opened, the bag can be folded out to reveal its neatly
- organised contents. • Multiple internal dividers and gear loops improve the kit's layout.
- A clear, external panel can be personalised to promote identification or used to list the bag's contents.
- Ergonomic shoulder straps and waist belt.
- Sternum strap with emergency whistle.
- Hauling loop at the top of the bag.
- 1 lateral carry handle.
- Reflective and fluorescent patches.
- PVC 1100 g/m².



Usage example (bag sold without contents)



COMBI PRO 80

Bag for professionals who require a large volume, yet maintaining quick and easy access to their kit.

STRONG POINTS

- Benefits from BEAL's 'QUICK RELEASE' system to accelerate access to the bag's contents via two back panel sections.
- Once opened, the bag can be folded out to reveal its neatly organised contents.
- Multiple internal dividers and gear loops improve the kit's lavout.
- The COMBI PRO 80's integrated rope bag contains a large ground sheet for immediate use of the rope without it twisting.
- A red buckle identifies the bottom end of the rope, whilst a green buckle identifies the top end.
- Lateral carry handle.
- Generously sized ground sheet 60 cm x 80 cm.
- Bag stores up to 60 m of rope.
- A clear, external panel can be personalised to promote identification or used to list the bag's contents.
- Ergonomic shoulder straps and waist belt.
- Sternum strap with emergency whistle.
- Hauling loop at the top of the bag.
- 1 lateral carry handle.
- Reflective and fluorescent patches.
- PVC 1100 g/m².



Usage example (bag sold without contents)









PRO RESCUE 40

Rescue bag ideal for rapid access operations. Capable of taking 30 metres 12,5 mm of rope and basic hardware.

STRONG POINTS

- Lid with transparent internal pocket to list contents.
- A clear, external panel can be personalised to promote
- identification.
- Adjustable shoulder straps.
- W ebbing loop under the bag to be able to guide it from the bottom via a 'tag line'.
- 1 removable, internal daisy chain gear loop.
- 1 lateral carry handle.
- Robust 650 g/m² PVC material.

Capacity	Weight	Height	Width
40 L	900 g	60 cm	30 cm



PRO RESCUE 60

Rescue bag ideal for rapid access operations. Capable of taking 60 metres 12,5 mm of rope and basic hardware.

STRONG POINTS

- Lid with transparent internal pocket to list contents.
- A clear, external panel can be personalised to promote identification
- Adjustable shoulder straps.
- W ebbing loop under the bag to be able to guide it from the bottom via a 'Tag line'.
- 1 removable, internal daisy chain gear loop.
- 1 lateral carry handle.
- Robust 650 g/m² PVC material.

Capacity	Weight	Height	Width
60 L	1000 g	60 cm	35 cm





 $<\beta>$

RESCUE KIT

Allows the evacuation of a person by the outside of a building or from a pit or a ditch, up to a height limit of 30 m. Equally useful in interventions at height or on horizontal progressions to protect against falls. Allows the same uses as the RESCUE KIT but with a carrying limit of 60 m.

PRO RESCUE 40





WORK STATION

Products within the WORK STATION range provide a complete solution for attaching and organising a work station. Different products from the range can be combined in a modular way to suit the work environment and users' needs: builders, rope access technicians, craftsmen...

GENIUS SIMPLE AND GENIUS TRIPLE

Bags for carrying small tools and fastenings.

The clic clac express closure stops the pocket contents getting lost. A magnetic plate allows temporary storage on the outside of the pocket.

Available as a single pocket and an assembly of 3 with external tool carriers.

STRONG POINTS

Express closure.

• Easy to attach to the

• Rigid opening. • Magnetic plate.





GENIUS BUCKET

A 20 litre bucket for carrying tools as well as small screws and fittings thanks to the 3 GENIUS CLIC CLAC pockets attached to the inside

The large opening with stiffener allows easy access to its contents. • Rigid carrying handle,

- STRONG POINTS Easy, convenient access to tools.
- CLIC CLAC pocket closure
- with a minimum breaking load of 100kg • Waterproof pocket. oase

• 'twist and fold' function

Comfortable and

to reduce size for storage

adjustable shoulder strap

helps to carry the bucket

system.			• Reinfo	orced bas
Capacity	Weight	Height	Width	Max. load
20 L	1085 g	40 cm	40 cm	50 kg

GENIUS BUCKET PLUS

A rigid 20 litre bucket for power tools such as a hammer drill, electric screwdriver or angle grinder; constructed with a clever 'twist and fold' function to reduce size for storage. Small gear loops on the outside and inside edges of the bag can be used to attach small CLIC CLAC pockets (TOOL BUCKET, GLASS BUCKET, LONG TOOL BUCKET) to organise your work station as you wish.

STRONG POINTS

- Easy, convenient access to tools
- Additional BUCKETs can be added
- Rigid carrying handle with a minimu n breaking load of

n minimum breaking load of 100kg			 Waterproof pocket Reinforced base 		
apacity	Weight	Height	Width	Max. load	
20 L	830 g	40 cm	40 cm	50 kg	



42



Сар

- **KEY FEATURES**
 - Improves posture, reducing the potential for physical iniurv
 - Improves efficiency by reducing unnecessary movement • Enhances safety by reducing the possibility of dropping work tools
 - Reduces costs by a reduction in loss of work tools







BUCKET HAT

A removable lid for the GENIUS BUCKET PLUS. Designed to protect items inside the GENIUS BUCKET PLUS from bad weather, dust etc. and to restrain the contents during transit and whilst hauling.

Fitted using clips.

Ref. BSAC.BH



GLASS BUCKET

A small transparent bucket for organising bolts, screws and other small items whilst leaving contents easily visible.

The CLIC CLAC system can be used to quickly close the bag and prevents loss of contents during transport.

2 external mini karabiners are fitted to connect the GLASS BUCKET to the GENIUS BUCKET, HERO PRO, SYNCRO and STYX harness or to the AIR-SIT work seat.





AL> PRO



TOOL BUCKET L

Large size tool organiser bucket.

The CLIC CLAC system can be used to quickly close the bag and prevents loss of contents during transport.

Two mini external gear loops can be used to connect another BUCKET from BEAL's range, an ATTRAC'TOOL magnet or an AIR-LEASH extendable gear holder.

Two external mini karabiners can be used to connect the LONG TOOL BUCKET to the HERO PRO, SYNCRO and STYX harness or to the AIR-SIT work seat.



TOOL BUCKET

Medium size tool organiser bucket.

LEASH extendable gear holder.

Weight

180 g

Heiaht

25 cm

Width

16 cm

the AIR-SIT work seat.

3,4 L

prevents loss of contents during transport.



Clic clac system







≤ß>



WORK STATION

T

AIR LEASH

An extendable gear loop allowing tools to remain attached whilst in use.

CONSISTS OF TWO SECTIONS

- An extendable spiral cord that attaches to the TOOL-BUCKET, GLASS BUCKET, LONG TOOL BUCKET, to the HERO PRO, SYNCRO and STYX harness, or the AIR-SIT work seat.
- A gear loop that connects to the end of the spiral cord. This is designed to attach tools by means of a girth hitch or slipknot (it is important you select an attachment method appropriate for the specific tool).

A reinforced webbing loop on the gear loop allows the tool to be clipped to the harness using a karabiner between uses

The gear loops are available separately. All tools equipped with gear loops can thus be independently connected to the spiral cord.



SUPER LEASH

A webbing based extendable gear loop allowing tools to remain attached whilst in use.

One end can be used to attach tools by means of a girth hitch or slipknot (it is important you select an attachment method appropriate for the specific tool).

The other end is equipped with a screwgate mini-karabiner for attachment to a tool pouch or gear loop.

Minimum	Weight	Max length with	Maximum
length		10 kg load	weight
70 cm	70 g	115 cm	10 kg





ATTRAC'TOOL

A magnetic plate that allows you to temporarily attach a leash secured tool to an appropriate metal surface.

The ATTRAC'TOOL can be fixed to a belt or shoulder strap of the HERO PRO harness or to the small gear loops of a harness, BUCKET or TOOL BELT.

When fitted to a harness' waist belt, a strap can be clipped around the thigh to stop the magnet from lifting up when picking up the tool. The strap can also be used to hang the ATTRAC'TOOL from a railing.

The ATTRAC'TOOL is modular and can be positioned both vertically and horizontally depending on the tools used and the working environment.







TOOL BELT

A waist belt with small gear loops for use with the TOOL BUCKET, LONG TOOL BUCKET, GLASS BUCKET, AIR LEASH and ATTRAC'TOOL.

Webbing gear loops positioned around the belt allow the tools to be secured where convenient.

The belt is reinforced to help spread out the weight of the tools on the waist.

Mini waist measurement	Maxi waist measurement	Width	Weight
70 mm	130 mm	50 mm	190 g





ROPE PROTECTORS

PROTECTOR

A rope can wear very rapidly over a sharp edge. To protect it, use the PROTECTOR, an ultra-solid rope protector made of two layers of coated material.

Length: 70 cm Weight: 150 g





MAGNETIC PROTECTOR

Rope protector reinforced on both sides by a tape for better abrasion resistance. Installation facilitated by a magnetic closure.

STRONG POINTS:

- Increased abrasion resistance.
- Easy to close thanks to its magnets.
- May be independently positioned on metallic surfaces.



Ref. BPRM











EDGE GUARD

Rope protector in stainless steel to protect a rope moving over a sharp edge.

STRONG POINTS:

- Modulable can be linked together with maillon rapides.
- Secure with 2 cords (supplied).
- 2 side plates prevent the rope from leaving the rail.

Weight: 300 g



ROPE DEFENDER

Flexible sleeve made from coiled steel which serves to protect ropes from sharp edges. Thanks to its flexibility, it adapts to all angles. The spirals that are in contact with the edge squeeze together under the rope's movement therefore ensuring total protection. The steel sleeve is virtually indestructible. Its reinforced rubber protecting cover exists as a separate part and may be easily replaced.

STRONG POINTS:

- Virtually indestructible steel sleeve.Removable protective cover.
- Length: 50 cm Weight: 730 g









CROCO

Universal clamp to secure different rope protectors onto a rope. The CROCO replaces the use of cord with a Prusik loop and other temporary attachment methods. Fitted with a cable and a small karabiner, it attaches easily to any rope protector on the market. Being independent of the rope protector, the CROCO can be reused when the rope protector has to be replaced.

STRONG POINTS:

- Adapts to all ropes from 9 to 12 mm.
- Attaches quickly to all rope rotectors
- on the market.
- Reusable.

Length: 23 cm Weight: 40 g



Ref. BPRCROCO





GLOVES AND ACCESSORIES



X 25

Ref. BRM